I CLAIM:

1. A lateral-view mirror assembly for a vehicle comprising, in combination:

a vehicle; and

at least one lateral-view mirror coupled to one of a rear portion and a rear window of said vehicle in line of sight with at least one of a side mirror of said vehicle and a rear-view mirror of said vehicle and dimensioned to allow a driver to view objects positioned lateral to a rear portion of said vehicle by looking at one of said side mirror and said rear-view mirror and seeing a reflection of said objects through said lateral-view mirror.

- 2. The assembly of Claim 1 wherein said at least one lateral-view mirror is coupled to said driver's side rear side portion of said vehicle.
- 3. The assembly of Claim 2 further comprising a second lateral-view mirror coupled to a passenger side of said vehicle proximate said rear portion of said vehicle in line of sight with a side mirror of said vehicle on said passenger side.
- 4. The assembly of Claim 3 further comprising a substantially flat mirror adapted to be coupled to a surface of said side mirror on said passenger side of said vehicle.

- 5. The assembly of Claim 1 wherein said at least one lateral-view mirror is adapted to be coupled to a center portion of a top surface of a rear portion of said vehicle, said lateral-view mirror is positioned in a line of sight with said rear-view mirror, said lateral-view mirror is dimensioned to allow a driver to view objects positioned lateral to one of a driver's side of a rear portion of said vehicle and lateral to a passenger's side of a rear portion of said vehicle by looking in a rear-view mirror within said vehicle at a reflection of said objects reflected from said lateral-view mirror.
- 6. The assembly of Claim 5 wherein said lateral-view mirror is dimensioned to allow a driver to selectively view objects positioned lateral to either of a driver's side of a rear portion of said vehicle and lateral to a passenger's side of a rear portion of said vehicle by looking in a rear-view mirror within said vehicle at a reflection of said objects reflected from said lateral-view mirror.
- 7. The assembly of Claim 5 further comprising a base coupled at a first end to said vehicle and at a second end to said lateral-view mirror and dimensioned to permit vertical movement of said lateral-view mirror.
- 8. The assembly of Claim 4 further comprising a base coupled at a first end to said vehicle and at a second end to said lateral-view mirror and dimensioned to permit rotational movement of said lateral-view mirror about a horizontal axis.

- 9. The assembly of Claim 7 wherein said base is further dimensioned to permit rotational movement of said lateral-view mirror about a horizontal axis.
- 10. The assembly of Claim 1 wherein said at least one lateral-view mirror comprises a first lateral-view mirror coupled to a top surface of a rear portion of said vehicle between a center portion of said top surface and a driver's side of said top surface, said first lateral-view mirror is positioned in a line of sight with said rear-view mirror, said first lateral-view mirror is dimensioned to allow a driver to view objects positioned lateral to said driver's side of a rear portion of said vehicle by looking at a reflection of said objects reflected from said first lateral-view mirror to said rear-view mirror to said driver; and

a second lateral view mirror distant from said first lateral-view mirror and coupled to a top surface of a rear portion of said vehicle between a center portion of said top surface and a passenger's side of said top surface, said second lateral-view mirror is positioned in a line of sight with said rear-view mirror, said second lateral-view mirror is dimensioned to allow a driver to view objects positioned lateral to a passenger's side of a rear portion of said vehicle by looking at a reflection of said objects reflected from said second lateral-view mirror to said driver.

11. The assembly of Claim 1 wherein said at least one lateral-view mirror comprises a first lateral-view mirror coupled to a rear window of said vehicle between a center portion of said rear window and a driver's side of said rear window, said first lateral-view mirror is positioned in a line of sight with said rear-view mirror, said first lateral-view mirror is dimensioned to allow a driver to view objects positioned lateral to said driver's side of a rear portion of said vehicle by looking at a reflection of said objects reflected from said first lateral-view mirror to said rear-view mirror to said driver; and

a second lateral-view mirror distant from said first lateral-view mirror and coupled to said rear window of said vehicle between said center portion of said rear window and a passenger's side of said rear window, said second lateral-view mirror is positioned in a line of sight with said rear-view mirror, said second lateral-view mirror is dimensioned to allow a driver to view objects positioned lateral to a passenger's side of a rear portion of said vehicle by looking at a reflection of said objects reflected from said second lateral-view mirror to said driver.

12. A lateral-view mirror assembly for a vehicle comprising, in combination:

a vehicle; and

portion of said vehicle in line of sight with a side mirror of said vehicle and dimensioned to allow a driver to view objects positioned lateral to a rear portion of said vehicle by looking at said side mirror and seeing a reflection of said objects through said lateral-view mirror.

- 13. The assembly of Claim 12 wherein said at least one lateral-view mirror is coupled to said driver's side rear side portion of said vehicle.
- 14. The assembly of Claim 13 further comprising a second lateral-view mirror coupled to a passenger side of said vehicle proximate said rear portion of said vehicle in line of sight with a side mirror of said vehicle on said passenger side.
- 15. The assembly of Claim 14 further comprising a substantially flat mirror adapted to be coupled to a surface of said side mirror on said passenger side of said vehicle.

18

Sub

П

16. A lateral-view mirror assembly for a vehicle comprising, in combination:

a vehicle; and

at least one lateral-view mirror coupled to a top rear portion of said vehicle in line of sight with a rear-view mirror of said vehicle and dimensioned to allow a driver to view objects positioned lateral to a rear portion of said vehicle by looking at said rear-view mirror and seeing a reflection of said objects through said lateral-view mirror.

- 17. The assembly of Claim 16 wherein said lateral-view mirror is dimensioned to allow a driver to selectively view objects positioned lateral to either of a driver's side of a rear portion of said vehicle and lateral to a passenger's side of a rear portion of said vehicle by looking in a rear-view mirror within said vehicle at a reflection of said objects reflected from said lateral-view mirror.
- 18. The assembly of Claim 16 further comprising a base coupled at a first end to said vehicle and at a second end to said /lateral-view mirror and dimensioned to permit vertical movement of said lateral-view mirror.
- 19. The assembly of Claim 18 wherein said base is further dimensioned to permit rotational movement of said lateral-view mirror about a horizontal axis.

20. A lateral-view assembly for a vehicle comprising, in combination:

a vehicle; and

means for capturing an image of an area rearward of and lateral to said vehicle and displaying said image to a driver of said vehicle.

add Bit